

City of Superior

2009 RIGHT-OF-WAY EXCAVATION PERMIT

Telephone: 395-7288

FAX: 395-7346

Fee: \$70.00

Permit No. _____

Date: _____

Fee Paid: _____

PERMIT EXPIRES ONE YEAR FROM DATE OF ISSUE

A PERMIT APPLICATION FEE OF \$30.00 IS REQUIRED BY ORDINANCE-INCLUDED

Applicant provide information in this block

APPLICANT: _____

MAILING ADDRESS: _____

TELEPHONE #: _____

PROJECT OWNER: _____

SITE LOCATION: _____

DESC. OF WORK _____

AREA TO BE EXCAVATED (ATTACH COMPUTATIONS): _____ SQ. YDS.

DATES EXCAVATION WILL OCCUR FROM: _____ TO: _____

APPLICANT: READ, SIGN, AND DATE THE REVERSE SIDE OF THIS FORM

ATTACH SKETCH OF EXCAVATION SHOWING THE FOLLOWING:

*EXISTING AND RESTORED PAVEMENT SECTION

*EXISTING AND RESTORED CROSS-SECTION OF EXCAVATION

*PROPOSED TYPE OF PAVEMENT AND BACKFILL MATERIALS TO BE USED IN RESTORATION

DO NOT WRITE IN THIS SECTION, PUBLIC WORKS USE ONLY

APPROVED BY: _____ DATE: _____

SPECIAL CONDITIONS _____

PRE-EXCAVATION INSPECTION CONDUCTED BY: _____ DATE: _____

ONE YEAR RESTORATION INSPECTED BY: _____ DATE: _____

INSPECTION CONDUCTED BY: _____ DATE: _____

COPIES PROVIDED TO: ENGINEERING _____
BUILDING INSPECTION _____
STREET DEPARTMENT _____

GENERAL CONDITIONS OF EXCAVATING PERMIT

Applicant agrees to and shall conform with the following general conditions and any special conditions listed on the permit approval.

1. Notification Requirements

Permittee shall contact the Public Works Department at 715-395-7333 48 hours prior to excavating within the Right of Way. The only exception to this requirement will be in the case of emergencies where such a delay will result in property damage or threaten health and safety. In the case of emergency Right of Way excavations, every effort should be made to contact the Public Works Department as soon as possible to obtain a permit.

Permittee shall contact the Public Works Department at 715-395-7333, 48 hour prior to conducting permanent restorations to pavement sections, curb, and gutter, and ditches or boulevard areas. There shall be no exceptions to this requirement. If permanent restorations cannot be conducted at the time of excavation due to weather conditions etc., permanent restorations must be completed within a maximum of six months from the time temporary restorations are completed.

2. Excavation and Restoration

A. Pavement Sections General

- a. Perimeter of excavations through pavement shall be saw cut only. Providing for a clean, straight edge.
- b. Pavement must be removed a minimum of twelve inches (12") beyond the area to be excavated.
- c. Backfill materials must be placed and compacted in six inch (6") lifts. Compaction to be to a minimum of 90% of proctor or modified proctor density. The City reserves the right to perform compaction tests during backfilling operations, materials not meeting the compaction requirements shall be reconditioned to meet the requirements. The final lift shall consist of ten inches (10") of 4 inch (4") minus and six inches (6") of grade 2 aggregate, placed and compacted.

B. Concrete Pavement Sections

- a. Drilled in steel reinforcing bar (#6) shall be placed into the existing pavement at a minimum of two feet (2') intervals on center along the perimeter of the saw cut. Replacements larger than ten square feet (10 sq. ft.) require steel mesh reinforcing be placed throughout the area and tied to the drilled in steel reinforcing bars.
- b. Replaced concrete must be a minimum of two inches (2") thicker than the existing pavement section. Concrete mix shall have a minimum 28 day design strength of 5000psi, or be shown to have a strength equal to or greater than the existing pavement section.
- c. Saw cut joint shall be placed to match existing joints, or at a minimum of ten foot (10') intervals.

C. Asphalt Pavement Sections

- a. If geo-textile fabric is present in the existing pavement section, it must be replaced.
- b. Asphalt pavement must be replaced with a minimum thickness four inches (4") or match to existing thickness if existing thickness exceeds four inches (4").
- c. Asphalt pavement must be replaced with a minimum of two lifts, the lower lifts consisting of an asphaltic design mix meeting WIDOT special gradation No. 2, the final lift consisting of a design mix meeting WIDOT special gradation No. 3.

D. Curb, Gutter Ditches and Boulevards

- a. Excavations which disrupt in any way, a drainage structure or boulevard, must be restored to the original conditions, i.e. slopes, grades, cross-sections, or profiles, and can in no way alter the original drainage pattern.

3. Warranty

The permittee shall guarantee the materials and workmanship of the permanent repair for a period of one year after such work has been inspected and approved by the Public Works Department. The level of work required to repair any failure of the restorations shall be determined by the Public Works Director or his designee.

Applicant's Signature _____ Date _____